



		Class	Weight
1	Cover according to standart EN124 (☒)	A35 (3,5 t) ☐	13 kg
		B125 (12,5 t) ☐	45 kg
		C250 (25 t) ☐	55 kg
		D400 (40 t) ☐	90 kg
2	Maintenance shaft (☒)	800...1000 ☐	31 kg
		1000...1250 ☐	33 kg
		1250...1500 ☐	42 kg
		1500...1750 ☐	52 kg
		1750...2000 ☐	62 kg
		2000...2250 ☐	71 kg
		2250...2500 ☐	80 kg
3	Ladder		
4	Storage capacity for grease	200 l	
5	Grease separation chamber	1200 l	
6	Sludge trap	570 l	
7	Grease level alarm sensor (☒)	☐	
	Nominal flow rate	4 l/s	
	Total capacity	1970 l	
	Weight excluding manhole shaft/lid	175 kg	

Product	GR	Name	Grease separator Greasly 4		Scale	1:50	
Design by	M.Skuzinskas	Checked by	E.Mozuraitis	Approved by	E.Kuodis	Drawing type	
						Customer drawing	
				Construction site		Drawing no.	
						Date	Lang.
						12/1/2015	en
							Sheet
							1



UAB EHEKA
 Vandziogalos g. 94 LT-47467 Kaunas,
 Lithuania
 tel. +37037377441, faks. +37037377907
 www.eneka.lt, info@eneka.lt