



1	Cover according to standard EN124 (☒)	Class	Weight	
		A35 (3,5 t) ☐	13 kg	
		B125 (12,5 t) ☐	45 kg	
		C250 (25 t) ☐	55 kg	
2	Maintenance shaft (☒)	D400 (40 t) ☐	90 kg	
		800...1000 ☐	31 kg	
		1000...1250 ☐	33 kg	
		1250...1500 ☐	42 kg	
		1500...1750 ☐	52 kg	
		1750...2000 ☐	62 kg	
		2000...2250 ☐	71 kg	
		2250...2500 ☐	80 kg	
3	Ladder			
4	Automatic closure			
5	Coalescing modules			
6	Sludge trap	6000 l		
7	Oil storage capacity	820 l		
8	Effective capacity	7200 l		
9	Bypass model	Sepko flow rate	D	Max flow rate
	B-30/3150 ☐	NS ≤30	315	90 l/s
	-	-	-	-
10	Oil level alarm sensor (☒)	☐		
	Nominal flow rate	30 l/s		
	Total capacity	13200 l		
	Weight excluding manhole shaft/lid	1850 kg		

Product Snigo	Name oil/water separator Sepko 30/6000	Scale 1:50
Design by M.Skuzinskas	Checked by E.Mozuraitis	Approved by E.Kuodis
Construction site -		Drawing type Customer drawing
Drawing no. -		Date 6/21/2016
 UAB ENKA Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.enka.lt, info@enka.lt		Lang. en
		Sheet 1