


1	Cover according to standard EN124 (☒)	Class	Weight
		A35 (3,5 t) ☐	13 kg
2	Maintenance shaft (☒)	B125 (12,5 t) ☐	45 kg
		C250 (25 t) ☐	55 kg
		D400 (40 t) ☐	90 kg
		800...1000 ☐	31 kg
		1000...1250 ☐	33 kg
		1250...1500 ☐	42 kg
		1500...1750 ☐	52 kg
2	Maintenance shaft (☒)	1750...2000 ☐	62 kg
		2000...2250 ☐	71 kg
		2250...2500 ☐	80 kg
3	Ladder		
4	Automatic closure		
5	Coalescing modules		
6	Sludge trap	6000 l	
7	Oil storage capacity	820 l	
8	Effective capacity	7200 l	
9	MPS sampling		
10	Closing valve DN250		
11	Oil level alarm sensor (☒)	☐	
		Nominal flow rate	30 l/s
		Total capacity	13200 l
		Weight excluding manhole shaft/lid	1650 kg

Product Snigo	Name Oil/water separator SEPKO 30/6000/MPS	Scale 1:50
Design by M.Skuzinskas	Checked by E.Mozuraitis	Approved by E.Kuodis
 UAB ENEKA Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.eneka.lt, info@eneka.lt		Drawing type Customer drawing Drawing no. - Date 8/31/2016
Construction site -		Lang. Sheet en 1