



1	Cover according to standard EN124 (☒)	Class	Weight
		A35 (3,5 t) ☐	13 kg
2	Maintenance shaft (☒)	B125 (12,5 t) ☐	45 kg
		C250 (25 t) ☐	55 kg
		D400 (40 t) ☐	90 kg
		800...1000 ☐	31 kg
		1000...1250 ☐	33 kg
		1250...1500 ☐	42 kg
3	Ladder	1500...1750 ☐	52 kg
		1750...2000 ☐	62 kg
		2000...2250 ☐	71 kg
		2250...2500 ☐	80 kg
		4	Automatic closure
5	Coalescing modules		
6	Sludge trap	10000 l	
7	Oil storage capacity	2700 l	
8	Effective capacity	12000 l	
9	Oil level alarm sensor (☒)	☐	
		Nominal flow rate	50 l/s
		Total capacity	27500 l
		Weight excluding manhole shaft/lid	2040 kg

Product NS	Name Oil/water separator SEPKO 50/10000	Scale 1:50
Design by M.Skužinskas	Checked by E.Mozūraitis	Approved by E.Kuodis
 UAB ENKA Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.eneka.lt, info@eneka.lt		Drawing type Customer drawing Drawing no. NS200-13-50BS Date 2015.09.14 Lang. en Sheet 1