



| | | Class | Weight |
|---|---------------------------------------|-----------------|--------|
| 1 | Cover according to standard EN124 (☒) | A35 (3,5 t) □ | 13 kg |
| | | B125 (12,5 t) □ | 45 kg |
| | | C250 (25 t) □ | 55 kg |
| | | D400 (40 t) □ | 90 kg |
| 2 | Maintenance shaft (☒) | 800...1000 □ | 31 kg |
| | | 1000...1250 □ | 33 kg |
| | | 1250...1500 □ | 42 kg |
| | | 1500...1750 □ | 52 kg |
| | | 1750...2000 □ | 62 kg |
| | | 2000...2250 □ | 71 kg |
| | | 2250...2500 □ | 80 kg |
| 3 | Ladder | | |
| 4 | Automatic closure | | |
| 5 | Coalescing modules | | |
| 6 | Sludge trap | 3000 l | |
| 7 | Oil storage capacity | 820 l | |
| 8 | Effective capacity | 7750 l | |
| 9 | Oil level alarm sensor (☒) | □ | |
| | Nominal flow rate | 30 l/s | |
| | Total capacity | 13300 l | |
| | Weight excluding manhole shaft/lid | 860 kg | |

| | | | | | |
|-----------|--------------|------------|-----------------------------------|-------------------|------------------|
| Product | NS | Name | Oil/water separator SEPKO 30/3000 | Scale | 1:50 |
| Design by | M.Skužinskas | Checked by | E.Mozūraitis | Approved by | E.Kuodis |
| | | | | Construction site | |
| | | | | Drawing type | Customer drawing |
| | | | | Drawing no. | - |
| | | | | Date | 2015.09.09 |
| | | | | Lang. | en |
| | | | | Sheet | 1 |



UAB ENKA
 Vandziogalos g. 94 LT-47467 Kaunas,
 Lithuania
 tel. +37037377441, faks. +37037377907
 www.enka.lt, info@enka.lt