



		Class	Weight	
1	Cover according to standard EN124 (☒)	A35 (3,5 t) □	13 kg	
		B125 (12,5 t) □	45 kg	
		C250 (25 t) □	55 kg	
		D400 (40 t) □	90 kg	
		800...1000 □	31 kg	
		1000...1250 □	33 kg	
		1250...1500 □	42 kg	
2	Maintenance shaft (☒)	1500...1750 □	52 kg	
		1750...2000 □	62 kg	
		2000...2250 □	71 kg	
		2250...2500 □	80 kg	
		3 Ladder		
		4 Automatic closure		
5 Coalescing modules				
6	Sludge trap	600		
7	Oil storage capacity	180 l		
8	Effective capacity	910 l		
9	Oil level alarm sensor (☒)	□		
		Nominal flow rate	3 l/s	
		Total capacity	1600 l	
		Weight excluding manhole shaft/lid	185 kg	

Product <b>NS</b>	Name <b>Oil/water separator SEPKO 3/600</b>	Scale <b>1:50</b>
Design by <b>M.Skužinskas</b>	Checked by <b>E.Mozūraitis</b>	Approved by <b>E.Kuodis</b>
 <b>UAB ENEKA</b> Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.eneka.lt, info@eneka.lt		Drawing type <b>Customer drawing</b>  Drawing no. <b>NS3-600-V-13-01BS</b> Date <b>10/31/2016</b>
Construction site		Lang. Sheet <b>en 1</b>