



1	Cover according to standard EN124 (☒)	Class	Weight
		A35 (3,5 t) ☐	13 kg
2	Maintenance shaft (☒)	B125 (12,5 t) ☐	45 kg
		C250 (25 t) ☐	55 kg
		D400 (40 t) ☐	90 kg
		800...1000 ☐	31 kg
		1000...1250 ☐	33 kg
		1250...1500 ☐	42 kg
2	Maintenance shaft (☒)	1500...1750 ☐	52 kg
		1750...2000 ☐	62 kg
		2000...2250 ☐	71 kg
		2250...2500 ☐	80 kg
		3	Ladder
4	Automatic closure		
5	Coalescing modules		
6	Sludge trap	4000	
7	Oil storage capacity	2200 l	
8	Effective capacity	9600 l	
9	Oil level alarm sensor (☒)	☐	
		Nominal flow rate	40 l/s
		Total capacity	16800 l
		Weight excluding manhole shaft/lid	1470 kg

Product	Name		Scale
NS	Oil/water separator SEPKO 40/4000		1:50
Design by	Checked by	Approved by	Drawing type
M.Skužinskas	E.Mozūraitis	E.Kuodis	Customer drawing
 UAB ENEKA Vandziogalos g. 94 LT-47467 Kaunas, Lithuania tel. +37037377441, faks. +37037377907 www.eneka.lt, info@eneka.lt		Construction site	Drawing no.
			NS100-13-40BS
Date	Lang.	Sheet	
2015.09.14	en	1	